

# POSIFLEX™

Leaders in POS Terminal Technology

*Powered By DreamPOS*







XT-2614Q is POSIFLEX's answer to the raising demands for the Android based POS terminal with all the features and capabilities of a traditional POS. It allows store owners to smoothly run the daily operation, while XT-2614Q delivers a low total cost of ownership and provides years of dependable operation.

## JIVA XT-2614Q

- Processor : Quad Core 1.0GHz
- System Memory : DDR3 1GB
- Storage Device :  
8GB eMMC + Micro SDD
- Power Supply : 12V / 40W
- OS support : Android 4.4
- Built-in WIFI : Optional
- LCD Display : 14" TFT LCD
- LCD Resolution : 1366 x 768
- Touch Function : TTrue-flat PCAP  
Touch with multi-touch support  
(IP65 on front panel)
- Audio : Internal 2W speaker x 1
- Standard USB Port : 3
- LAN Port : 10/100/1000 Mb x 1
- Weight : Approx. 4 kg
- Dimension : 271.2 x 371.6 x 252



## MT - 4008W

- An 8" tablet that can transform into a compact all-in-one POS terminal when paired with the optional integrated pistol grip and printer docking station. The MT4008 system is modular with maximum flexibility to configure as needed.
- Projected capacitive touch
- 1024x768 screen resolution
- Windows 8.1 Industrial Pro
- 60% smaller than typical POS setup\*
- WiFi in tablet for wireless printing to docking station
- MSR and handstrap included

### Options

- Pistol grip, which features:
  - Removable battery for 2x longer tablet power
  - 1D or 2D scanner
- Encryption Capable 3 Track MSR
- Docking Station with built-in wireless 3" thermal printer, 200mm/sec print speed

## FAN FREE TERMINAL

No Dust, No Need to bother cleaning it



## PS 3315E

- 15" fanfree touch terminal, with 7th gen. base Bay Trail quad core J1900
- Memory 2GB DDR3L 64G SSD
- 15" TFT LCD (1024x768) Resistive N
- Only support Windows 7/Posready 7/Windows embedded Industry 8.1, and DOS



## JIVA XT - 3815/17

- Processor : Intel Bay Trail Quad Core Celeron J1900, 2GHz up to 2.42GHz, 2M Cache
- System Memory :  
DDR3L 1333MHz SO-DIMM x 1, max. 8GB
- Storage : SATA Storage x 2 (one for HDD/SSD; the other for 1" SSD only) or Optional eMMC module
- Power Supply : 12V / 60W
- OS support : Windows 7/WE POSReady 7/WE 8.1 Industry/DOS /Linux per request
- LCD Display : 15"/17" TFT LCD
- LCD Resolution : 1024 x 768
- Touch Function : True-flat PCAP touch with 10 pts multi-touch support (IP65 on front panel)

## JIVA XT - 5315/17

- Intel Celeron G1820 / 2.7 GHz / 2M Cache
- Intel Pentium G3320TE / 2.3GHz / 3M Cache
- Intel Core i3 - 4430 TE / 2.4 GHz / 4M Cache
- System Memory :  
DDR3 1333 / 1600 SO-DIMM x 2, max. 16GB
- Storage Device : SATA storage x 2
- LCD Display : 15"/17" TFT LCD
- LCD Resolution : 1280 x 1024 resolution
- Standard USB Port :  
8 (USB 3.0 / 2.0 x 2 + USB 2.0 x 6)
- OS support : Windows 7 / POSReady 7 / Windows Embedded 8.1 Industry / Linux per request
- Power Supply : 12V / 130W



## PS 3415E

- 15" fanfree bezelfree PCAP touch terminal, with 7th gen. base Bay Trail quad core J1900
- Memory 2GB DDR3L 64G SSD
- 15" TFT LCD (1024x768) PCAP N
- Only support Windows 7/Posready 7/Windows embedded Industry 8.1, and DOS







Your Success  
is Our Vision



## JIVA KS 7410/ 7412

- LCD Display : 10"/12" Fanfree touch terminal
- Processor : Intel Quad core (J1900), 2M cache
- LCD Resolution : (1024x768)
- Power Supply : 60W PSU
- Memory : 2G DDR3L 320GB HDD
- Touch Function : PCAP touch



## BARCODE SCANNER LS 3000U

- Entry level 1D laser scanner
- Light source: 650 nm visible laser diode
- Scan Rate: Up to 120 scan / sec
- Interface: USB
- Barcode Support: Code 128, UCC/EAN 128, Code 93, UPC-A, UPC-E, EAN-13, EAN-8, ISBN/ISSN, Code 39 (ASCII full code), Code 25 Industrial, Matrix 25, Codabar, Code 11, MSI, Post Code

## POSIFLEX CUSTOMER POLE DISPLAY PD-2600



- Highly bright VFD with green or blue filter
- Two-line display with 20 characters per line
- Adequate character size per digit for easy viewing : 9.03 x 5.25 mm
- 15°, 30° and 45° adjustable view angles vertically
- Rotated display frame 270° horizontally
- Various command emulation modes selection by DIP switch



AURA 9000



AURA 8800



AURA 5200

## POSIFLEX COMPACT POSPrinter - AURA 7000

- The new Aura 7000 thermal receipt printer by POSIFLEX offers the performance, innovation, and affordability that you have come to expect.
- 180 mm/sec high-speed printer with 2MB flash memory
- Guillotine type auto cutter
- Clam-shell, drop and load design for easy paper loading and print head cleaning
- Light weight, quiet and compact
- Supports bar code printing international character sets and other languages.

## POSIFLEX CUSTOMER POLE DISPLAY PD-2800/PD-320



- Adjustable pole height
- PD-2800 series : Bright VFD (Vacuum Fluorescent Display) with green or blue filter
- PD-320 series : LCD display with blue character and yellow background
- Two-line display with 20 characters per line
- Adequate character size : 9.03 Å—5.25 mm (PD-2800 series), 6.0 Å—9.6 mm (PD-320 series)
- 15° and 23° adjustable view angles vertically

## POSIFLEX CASH DRAWER CR-4000/CR-4001

Specifications: The CR-4000 / 4001 series are midrange cash drawers, and wider, deeper, longer than the CR-3100 series. Boasting their high reliability and durability, the CR-4000 / 4100 series have screwless tamper-resistant design and robust case. They comes with 9 coin and 5 bill compartments for more multi-bill



## POSIFLEX PROGRAMMABLE POS Keyboard KB-6600

Powerful programming capability. True spill-resistant design. Optional blank key, double key for alternative key group layout. 84 programmable keys + 6 position control key. Interface : PS/2 (KB-6600) or USB (KB-6600U)

## POSIFLEX PROGRAMMABLE MSR2000

Built-in keyboard wedge interface or RS232 interface or USB interface as indicated in MODEL. Built-in decoder. Dual directional operation. Tracks Applicable 1 & 2. Interface Cable Included.





# POSIFLEX™

Leaders in POS Terminal Technology



## JIVA HS-3510/12/14 W

- Processor : Intel Bay Trail J1900, 4C, 2.00 GHz / 2.42 GHz (Burst)
- System Memory :  
DDR3L 1333MHz SO-DIMM x 1, max. 8GB
- Storage Device : SATA Storage x 2  
(one for HDD/SSD; the other for 1" SSD only)
- Power Supply : 24V / 60W
- OS support : Windows 7 / POSReady 7 /  
Windows Embedded 8.1 Industry /  
Windows 10 IoT/ Linux per request
- Standard USB Port :  
4, 1 x USB 3.0/2.0 + 3 x USB 2.0
- LCD Display : 9.7" TFT LCD
- Resolution : 1024 x 768



PT.Pratama Cipta Lestarindo  
Komplek Gading Bukit Indah Blok SB-1  
Jl.Bukit Gading Raya, Jakarta - 14240  
Phone: 021-290-788-58  
Fax: 021-290-788-18

[www.posiflex-pos.com](http://www.posiflex-pos.com)